

33P_{LED}

Low Profile Luminaire

Stainless steel, brass, aluminum.
31 - 42" adjustable height 787 - 1067mm.
Dome base and shield shown polished chromium.
P Shield rotates 360° horizontally
on dual vertical pivoting control tube.
Stem with dome base rotates 700° between stops.
Dome base folds 90° for compact shipment.

LED array specifications:

- ✧ New planar P shield is milled to a slim 5/16" and holds 48 high brightness 3500K Nichia LEDs.
- ✧ A low brightness louver prevents glare while it protects the LED array.
- ✧ A programmed microprocessor provides thermal regulation and wide range PWM dimming.

36 Volt DC power specifications:

- ✧ The included *international power supply* is included it delivers 36v DC from standard US 110-125 VAC as well as international voltages from 90 to 240 VAC.
- ✧ Cord from power source to Power Supply.
125 VAC Cord: 6' Black (UL)SVT 75°C.
- ✧ Cord from Power Supply to Luminaire:
36v DC Cord: 9' slender red or linen colored braid.

Uses less than 20w for diffuse task light.
Without 75-100w incandescent heat issues.
The ultimate green lighting device.
Cool!

Adjustable stance feet retracted
for hard floor installation

© Cedric Hartman 2009
All rights reserved

