



33 WV LED

Low Profile Luminaire

No Loop version shown

Adjustable stance feet at widest setting.

Stainless steel, brass, aluminum.

31 - 42" adjustable height 787 - 1067mm.

Dome base and shield shown in 24k gold plate.

Shields P and WV rotates 360° horizontally on dual vertical pivot control tube.

Stem with dome base rotates 700° between stops.

Dome base folds 90° for compact shipment.

Adjustable stance feet:

Retractable geared feet move in or out to support very small (5" diam) base on hard floors to medium pile carpet. Inquire for deep pile/shag conditions. Special strategies may be available.

36 volt DC LED Shield:

Two options, shapes milled from aluminum:

Planar P shield (at left) a slim 5/16" plate; and

the new WV shield (at right) thinner and sleeker (than our original from the mid 1960's)

Each holds 48 high brightness 3500K Nichia LEDs.

A magnetic low brightness louver prevents glare.

A programmed microprocessor provides thermal regulation and wide range PWM dimming.

*36 Volt DC Power

*The included *international power supply* delivers 36v DC from standard US 110-125 VAC as well as International voltages from 90 to 240 VAC.

*Cord from power source to Power Supply.

*125 VAC Cord: 6' Black (UL)SVT 75°C.

*Cord from Power Supply to Luminaire:

* 36v DC Cord: 9' slender red or linen colored braid.

Uses less than 20w for broad diffuse task light.

Eliminates incandescent 75-100w heat issues.

The ultimate green lighting device.

Cool.

©Cedric Hartman 2009

All rights reserved