

4VWVLED

Vertical Surface Mount Luminaire

Stainless steel, brass, aluminum.

WV Reflector shield:

Reflector rotates 360° on socket

Socket rotates 180° on vertical pivot

Stem rotates up to 670°*

Height Adjustment Range:†

As shown: Stem moves 17" [432mm]
from lowest position

*LED version 36 volt DC:

New ultra flat WVLED shield is milled from solid aluminum after our original 1965 WV reflector. It holds 48 high brightness 3500K Nichia LEDs. A magnetic low brightness louver prevents glare. A programmed microprocessor provides thermal regulation and wide range PWM dimming.

†36 Volt DC Power

*The included *international power supply* delivers 36v DC from standard US 110-125 VAC as well as international voltages from 90 to 240 VAC.

†Cord from power source to Power Supply.

*125 VAC Cord: 6' Black (UL)SVT 75°C.

†Cord from Power Supply to Luminaire:

* 36v DC Cord: 9' slender red or linen colored braid.

Uses less than 20w for diffuse task light.

Without 75-100w incandescent heat issues.

The ultimate green lighting device.

Cool!

†Custom versions:

Stem rotation and height adjustment may be specified to meet installation-specific variables.

Inquire for details

© Cedric Hartman 2009

All rights reserved

